

TECHNICAL DATA

Scapa 3101

Waterproof Cloth Tape

DESCRIPTION

Scapa 3101 is a premium performance, strong, waterproof cloth tape, coated with a pressure sensitive adhesive.

Scapa 3101 is available in a full range of colours including black, white, silver, grey, red, yellow, blue, green and brown.

APPLICATIONS

- Heavy duty and export packaging
- Sealing, protecting and strengthening general purpose applications
- Carpet jointing •
- Book and spine binding
- Colour coding and identification
- Joining and splicing applications
- Ideal for technical or demanding applications

PRODUCT BENEFITS

- Excellent waterproof properties
- Very strong and robust
- Flexible and highly conformable
- Good abrasion resistance
- Good corrosion resistance
- Easy unwind
- Can be written on
- Easy tear
- Low sulphur and halogen content
- Good low temperature performance
- Can be supplied to DEF STAN 81/25-3 on specific request
- Service Temperature of 0 to +60 °C

Issue : 2

Date : 02/12/02

Page 2 of 2

3101.doc

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whalsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer

TECHNICAL PROPERTIES

	Unit	Nominal Value	Test Method
Thickness	mm	0.3	Internal*
Tensile Strength	N/cm	78.5	IEC 454-2
Adhesion to Steel	N/cm	4.4	IEC 454-2
Adhesion to Backing	N/cm	3.0	IEC 454-2

STANDARD PRESENTATION

- Roll Length: 25m, 50m
- Roll Width: 19mm, 25mm, 38mm, 50mm, 75mm, 100mm
- Core: Cardboard
- Packaging: Scapa branded, bulk packed using interleaving sheets between layers.

Note: Information on stock items, non-standard sizes, and lead times is available on request

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Service life will vary with conditions of use and is affected by climatic environment, but should not be less than two years from date of manufacture, if stored in a moderate climate and good conditions. Usage is recommended within one year.

Issue : 2

Date : -2/12/02

Page 2 of 2

3101.doc

www.scapa.com

The information supplied is accurate to the best of Scapa's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, it shall not, it shall not, it shall not, its shall not extinctly arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. Freedom from Patent Rights must not be assumed. This document does not form part of any contract with a customer.